



Maximum Performance



MID-PERFORMANCE RANGE

UNIMAC.COM

UW45 - UW130 POCKET HARDMOUNT WASHER-EXTRACTORS

PRICED TO PERFORM.

As the leading manufacturer of on-premises laundry equipment, UniMac® offers more than seven decades of incomparable quality and long-lasting performance. Our UW series is built with unyielding construction to ensure industrial strength. Our cutting-edge innovations and technologies reduce costs and maximize throughput. And we're constantly improving. It's all part of our commitment to providing the lowest cost of ownership in the industry.

UniMac's Mid-Performance range of UW washer-extractors has all the hallmarks of the brand's legendary durability, and are designed for laundries requiring less robust feature sets – that means you get exceptional value for your money. Offered in 45- through 130-pound capacity models, the UW Mid-Performance line is engineered to deliver excellent wash results without sacrificing quality.

A ten-year warranty protects bearings, seals, frame, and cylinder shaft assembly from failure or breakage during normal operation due to defects in material or workmanship. A limited three-year warranty is offered on all other parts.



UW SERIES – AT A GLANCE.



**EXCELLENT VALUE
FOR YOUR DOLLAR**



**INDUSTRY-LEADING
QUALITY BACKED WITH
PEACE OF MIND**



**ROBOTICALLY
WELDED FRAME**



**AUTO LEAK
DETECTION**

- Industrial construction is built to run 24/7
- Helps reduce drying time and increase throughput with a 200 g-force extraction
- Bigger motor has 67% more horsepower than cabinet washer-extractors
- Handles unbalanced loads effortlessly
- UW 45/65 is 34.12" wide and easily fits through 36" commercial doorways
- 30 Programmable cycles
- Perforated cylinder ribs maximize wash action
- Auto leak detection greatly reduces water loss due to valve blockages or failures
- Simple installation with vertical access to frame bolts



Proudly based in Ripon, Wisconsin, USA, UniMac is dedicated to research, development and testing to provide equipment that delivers industrial strength and long-lasting quality. Our products undergo a 5-stage product development process and are pushed beyond their limits in our state-of-the-art test lab to ensure they exceed the toughest demands of the commercial environment and meet our customers' highest standards.

UW HARDMOUNT WASHER-EXTRACTORS 45-130LB

SPECIFICATIONS			UWT045		UWT065		UWT085	UWT105	UWT130
Control Option			M30		M30		M30	M30	M30
Capacity - lb (kg)			45 (20.4)		65 (29.5)		85 (38.6)	105 (47.6)	130 (59)
Cylinder Diameter - in (mm)			31 (787)		31 (781)		36 (914)	36 (914)	42 (1067)
Cylinder Depth - in (mm)			16.6 (422)		22.1 (561)		22 (559)	27 (686)	24.5 (622)
Cylinder Volume - cu ft (liters)			7.3 (185)		9.7 (246)		13 (368)	15.9 (450)	19.6 (555)
Width - in (mm)			34.1 (867)		34.1 (867)		40.1 (1019)	40.1 (1019)	46.1 (1171)
Depth - in (mm)			45.3 (1151)		51.1 (1298)		51.2 (1300)	56.2 (1427)	54.5 (1384)
Height - in (mm)			64.4 (1637)		64.4 (1637)		69.1 (1755)	69.1 (1755)	72.1 (1932)
Door Opening Size - in (mm)			17.8 (452)		17.8 (452)		21 (533)	21 (533)	24.8 (630)
Door Bottom to Floor - in (mm)			28.8 (732)		28.8 (732)		28.8 (732)	28.8 (732)	30.5 (775)
Motor Power - HP (kW)			5 (3.7)		5 (3.7)		7.5 (5.6)	7.5 (5.6)	10 (7.5)
Total # of Speeds			L Sp	M Sp	L Sp	M Sp	M Sp	M Sp	M Sp
			5	6	5	6	7	7	7
Cylinder Speed RPM (G-Force)*	Gentle		30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)	28 (0.4)	28 (0.4)	26 (0.4)
	Wash		42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)	39 (0.78)	39 (0.78)	36 (0.77)
	Distribution		75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	70 (2.5)	70 (2.5)	65 (2.5)
	Very Low Extract		248 (27)	248 (27)	248 (27)	248 (27)	230 (27)	230 (27)	213 (27)
	Low Extract		477 (100)	477 (100)	477 (100)	477 (100)	443 (100)	443 (100)	410 (100)
	Medium		–	674 (200)	–	674 (200)	542 (150)	542 (150)	502 (150)
	High		–	–	–	–	626 (200)	626 (200)	579 (200)
Voltage/ Circuit Breaker FLA**	X	200-240/50-60/1-3	15-6 (3 Ph) 15-8 (1 Ph)	15-8 (3 Ph) 15-11 (1Ph)	15-7 (3 Ph) 15-12 (1Ph)	15-9 (3 Ph) 20-16 (1 Ph)	–	–	–
	Q	200-240/50-60/3	–	–	–	–	20-14 (3 Ph)	20-14 (3 Ph)	20-16 (3 Ph)
Drain Diameter - in (mm)			1 x 3 (76)		1 x 3 (76)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Steam Connection - in (mm)			½ (13)		½ (13)		½ (13)	½ (13)	¾ (19)
Water Inlet Connection - in (mm)			2 x 0.75 (19)		2 x 0.75 (19)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 1 (25)
Shipping Dimensions - in (mm)	Width		37.2 (945)		37.2 (945)		43.2 (1097)	43.2 (1097)	49.2 (1250)
	Depth		53.8 (1370)		53.8 (1370)		61.8 (1570)	61.8 (1570)	64.8 (1646)
	Height		65 (1650)		65 (1650)		69.4 (1763)	69.4 (1763)	76.4 (1941)
Net Weight - lb (kg)			1080 (490)		1110 (499)		1670 (757)	1700 (771)	2040 (925)
Standard Shipping Weight - lb (kg)			1120 (508)		1150 (522)		1720 (780)	1750 (794)	2100 (953)
Slat Crate Shipping Weight - lb (kg)			1250 (567)		1280 (581)		1870 (848)	1900 (862)	2260 (1025)
Agency Approvals			cULus		cULus		cULus	cULus	cULus

* All RPM and G-Force results are reliant upon wash load composition and incoming voltage.

** For additional voltage information, please refer to the intallation guide.

TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.