



Maximum Performance



## ENGINEERED FOR EVERYDAY DEMANDS.

Not every laundry requires a fully industrial solution. Value Line hardmounts deliver 200 G-Force extraction to reduce drying time, fast drain cycles, and 30-, 40-, and 55-lb capacity options.

- 6 cycle control
- 200 G-Force
- Stainless steel cylinder and tub
- Anthracite gray front and side panels
- Liquid soap connection, 4 signal soap board & top load soap box
- Large drain valve
- Front access to vital parts for easy maintenance
- 3 water inlets

### LIMITED WARRANTY

- 1-Year: door seal gaskets, water valve diaphragms, belts and internal hoses
- 5-Years: frame, cylinder shaft and bearings
- 3-Years: any parts not listed above

UNIMAC.COM

VALUE LINE CABINET HARDMOUNT WASHER-EXTRACTOR

# VALUE LINE CABINET HARDMOUNT WASHER-EXTRACTOR

SPECIFICATIONS		UAT030 UAT030GN0MZAMPD0AA*	UAT040 UAT040GN0MZAMPD0AA*	UAT055 UAT055GN0MZAMPD0AA*
Control Option		6 Cycle	6 Cycle	6 Cycle
Capacity - lb (kg)		30 (13.5)	40 (18)	55 (24)
Overall Width - in (mm)		29.53 (750)	35.03 (890)	35.03 (890)
Overall Depth - in (mm)		35.43 (900)	36.02 (915)	41.73 (1060)
Overall Height - in (mm)		48.22 (1225)	55.51 (1410)	55.51 (1410)
Cylinder Diameter - in (mm)		24.40 (620)	29.53 (750)	29.53 (750)
Cylinder Depth - in (mm)		17.72 (450)	16.14 (410)	21.46 (545)
Cylinder Volume - cu ft (liters)		4.8 (135)	6.4 (180)	8.5 (240)
Door Opening Size - in (mm)		16.14 (410)	18.11 (460)	18.11 (460)
Door Bottom to Floor - in (mm)		13.46 (342)	18.31 (465)	18.31 (465)
Water Inlet Connection - in (mm)		3 x 0.75 (19)	3 x 0.75 (19)	3 x 0.75 (19)
Drain Diameter - in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Center Height to Floor - in (mm)		3.85 (98)	5.12 (130)	5.12 (130)
Motor - HP (kW)		1 (0.75)	1.48 (1.1)	2.01 (1.5)
Cylinder Speeds		Wash - RPM	46	42
		RPM (G-Force)	760 (200)	690 (200)
Voltage/ Circuit Breaker - FLA	Z	208-240/60/1	10 - 7.2	15 - 9.1
Shipping Dimensions - in (mm)		Width	31.5 (800)	36.42 (925)
		Depth	37.4 (950)	38.19 (970)
		Height	53.35 (1355)	61.02 (1550)
Net Weight - lb (kg)		419 (190)	695 (315)	728 (330)
Shipping Weight - lb (kg)		441 (200)	739 (335)	783 (355)
Agency Approvals		UL	UL	UL

\* 7.9" base available

**TO LEARN MORE, VISIT UNIMAC.COM OR CALL 1.800.587.5458. ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.